



Product Spec Sheet  
 Multitrack Recording Console  
**Model 2400**



■ **Specifications**

**Recorder specifications**

**Supported media**

- SD cards (Class 10 or higher)
- SDHC cards (Class 10 or higher)
- SDXC cards (512 GB maximum, Class 10 or higher)

**File System**

SD card:	FAT16
SDHC card:	FAT32
SDXC card:	exFAT

**Recording file formats**

WAV (BWF):	44.1/48kHz, 16/24-bit (Maximum file size: 2 GB)
------------	---

**Playback file formats**

WAV (BWF):	44.1/48kHz, 16/24-bit
------------	-----------------------

**Recordable Channel**

Max. 24 channels (22ch + 2 stereo mix)

**Inputs and outputs****Analog audio input and output ratings****MIC input jacks (1–12, 13, 15, 17, 19)**

Connectors:	XLR combo jacks XLR-3–31 equivalent (1: GND, 2: HOT, 3: COLD)
Maximum input level:	+10 dBu
Nominal input level:	–8 dBu
Minimum input level:	–58 dBu
Gain adjustment range:	0 – 50 dB
Input impedance:	1.9 k $\Omega$ (1–12), 2.4 k $\Omega$ (13, 15, 17, 19)

**LINE/INST input jacks (1–2)**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
Maximum input level:	+22 dBu (LINE)/19.8 dBV (INST)
Nominal input level:	+4 dBu (LINE)/ 1.8 dBV (INST)
Gain adjustment range:	–10 – +40 dB
Input impedance:	22 k $\Omega$ (LINE)/1 M $\Omega$ (INST)

**LINE input jacks (3–12)**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
Maximum input level:	+22 dBu
Nominal input level:	+4 dBu
Gain adjustment range:	–10 – +40 dB
Input impedance:	22 k $\Omega$ or higher

**LINE L/MONO, R input jacks (13/14–21/22)**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
Maximum input level:	+22 dBu
Nominal input level:	+4 dBu
Gain adjustment range:	–20 – +30 dB
Input impedance:	11 k $\Omega$ or higher (Mono), 22 k $\Omega$ or higher (Stereo)

**INSERT jacks (1–12)**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
RETURN (Ring)	
Maximum input level:	+18 dBu
Nominal input level:	0 dBu
Input impedance:	15 k $\Omega$
SEND (Tip)	
Maximum output level:	+18 dBu
Nominal output level:	0 dBu
Output impedance:	100 $\Omega$

**TALKBACK input jack**

Connectors:	XLR-3-31 equivalent (1: GND, 2: HOT, 3: COLD)
Maximum input level:	-22 dBu
Minimum input level:	-65 dBu
Gain adjustment range:	52 dB
Input impedance:	2.6 k $\Omega$ or higher

**MAIN OUTPUT L/R jacks**

Connectors:	XLR-3-32 equivalent (1: GND, 2: HOT, 3: COLD)
Maximum output level:	+22 dBu
Nominal output level:	+4 dBu
Output impedance:	200 $\Omega$

**MAIN SEND/RETURN L/R jacks**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: SEND, Ring: RETURN, Sleeve: GND)
RETURN (Ring)	
Maximum input level:	+18 dBu
Nominal input level:	0 dBu
Input impedance:	9 k $\Omega$ or higher
SEND (Tip)	
Maximum output level:	+18 dBu
Nominal output level:	0 dBu
Output impedance:	100 $\Omega$

**CONTROL ROOM L/R jacks**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
Maximum output level:	+16 dBu
Nominal output level:	-2 dBu
Output impedance:	200 $\Omega$

**AUX OUTPUT jacks (1-5)**

Connectors:	6.3mm (1/4") standard TRS jacks Tip: HOT, Ring: COLD, Sleeve: GND)
Maximum output level:	+16 dBu
Nominal output level:	-2 dBu
output impedance:	200 $\Omega$

**SUB OUTPUT jacks (1-2/3-4/5-6/7-8)**

Connectors:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
Maximum output level:	+16 dBu
Nominal output level:	-2 dBu
Output impedance:	200 $\Omega$

**PHONES jack**

Connectors:	6.3mm (1/4") standard stereo jack
Maximum output:	80mW + 80mW (32 $\Omega$ load)

**Control input/output****USB port**

Connector:	USB Type-B
Protocol:	USB 2.0 HIGH SPEED (480 Mbps)

**CLICK jack**

Connector:	6.3mm (1/4") standard TRS jacks (Tip: HOT, Ring: COLD, Sleeve: GND)
------------	---

**FOOTSWITCH jack**

Connector:	6.3mm (1/4") standard TRS jacks (Tip: FOOTSW1, Ring: FOOTSW2, Sleeve: GND, Unlatch type correspondence)
------------	--

**MIDI OUT connector**

Connector:	5-pin DIN
Format:	standard MIDI

**MIDI IN connector**

Connector: 5-pin DIN  
Format: standard MIDI

**Operating system and computer requirements**

Check the TEAC Global Site (<http://teac-global.com/>) for the latest information about supported operating systems.

**ATTENTION**

Operation with each OS was confirmed with standard system setups that met the following conditions. Operation is not guaranteed, however, with all systems that meet the following conditions.

**Windows****Supported operating systems**

Windows 11  
Windows 10 64-bit

**Computer hardware requirements**

Windows computer with a USB 2.0 (or higher) port

- Using the TASCAM driver
- Operation not guaranteed with ARM64 CPUs

**Mac****Supported operating systems**

macOS Sonoma (14)  
macOS Ventura (13)

**Computer hardware requirements**

Mac with a USB 2.0 port

**iOS/iPadOS devices**

iOS 17/iPadOS 17  
iOS 16/iPadOS 16

**NOTE**

To connect an iOS device that has a Lightning connector, a genuine Apple Lightning to USB Camera Adapter (sold separately) is necessary.

A USB cable is necessary when connecting to an iOS device that has a USB Type-C connector.

**Settings Panel (application)****Windows**

Windows 11  
Windows 10 64-bit

**Mac**

macOS Sonoma (14)  
macOS Ventura (13)

**Screen resolution/number of colors**

1280 × 720 or higher  
True Color (32-bit) recommended

**Audio performance****Noise**

Residual output noise (22 kHz, A-weighted)

MAIN MIX OUT : (ALL Fader MIN, MAIN MIX OFF) -100 dBu

**Equivalent input noise (EIN)**

-128 dBu (Rs = 15 Ω, MIC IN w INSERT SEND, gain knob at MAX, A-weighted)

**Total harmonic distortion ratio (THD+N)**

(GAIN knob at MIN, 1kHz)

MIC IN → MAIN OUT: 0.01% or less  
 MIC IN → MAIN OUT: 0.004% @ (+2 dBu, BYPASS switches on)

**Frequency response**

(All GAIN knobs minimized, 1 kHz )  
 20Hz to 30kHz (+0.5/-1.0dB: Analog)  
 20Hz to 20kHz (+0.5/-1.0dB: Digital)

**Crosstalk**

(1 kHz BPF)  
 Between channels: -80 dB

**Maximum gain**

(All GAIN knobs maximized, PAN knobs turned completely left or right, BYPASS switches on, MASTER BUS IN switch off)

MIC → MAIN OUT: 74 dB  
 MIC → INSERT OUT: 54 dB  
 MIC → SUB OUT: 74 dB  
 MIC → AUX OUT: 75 dB  
 USB/SD → MAIN OUT: 24 dB

**Recording times**

Recording format	Recording time (hours: minutes) for 32GB card
16-bit/44.1 kHz WAV, 24 tracks	4:10
16-bit/48 kHz WAV, 24 tracks	3:50
24-bit/44.1 kHz WAV, 24 tracks	2:47
24-bit/48 kHz WAV, 24 tracks	2:33

●The recording times shown above are estimates. They might differ depending on the SD card in use.

**Bluetooth**

Bluetooth version: 5.1

Output class: 2 (about 10m\* unobstructed transmission distance)  
 Supported profiles: A2DP  
 Supported A2DP codecs: SBC, AAC  
 Supported A2DP content protection: SCMS-T

\* The transmission distance is only an estimate and might vary depending on the surrounding environment and radio wave conditions.

**Other**

**Power**

AC100-240V, 50/60 Hz

**Power consumption**

65W

**Dimensions**

With side panels  
 680.5 × 132.5 × 568.0 mm (W x H x D, including protrusions)  
 Without side panels  
 638.5 × 132.5 × 568.0 mm (W x H x D, including protrusions)

**Weight**

14kg


**Guaranteed operating temperature range**

0 – 40° C (32 – 104° F)

**Guaranteed operating humidity range**

5 – 85% (without condensation)

■ **Dimensional drawings**



※TASCAM is trademark of TEAC CORPORATION, registered in the U.S. and other countries.

※Other company names, product names and logos are the trademarks or registered trademarks of their owners.

※Specifications and appearance are subject to change without notice.

※All information included in this document is as of Jul, 2024.