

Please correct the specifications on pages 15 and 16 of the *Owner's Manual* and on page 8 of the *Setup Guide* as follows:

Analog I/O**INSERT Return**

Input impedance 10 k ohm

Digital I/O**ADAT/OPTICAL input**

Format ADAT/IEC60958

ADAT/OPTICAL output

Format ADAT/IEC60958

Analog performance**THD (at maximum input level)**

< 0.010% (Hi FS) 1 kHz, MIC/LINE IN to STEREO OUT

Frequency response (at nominal level)

20 Hz - 40 kHz (Hi FS) +0.5 dB/-2.0 dB, MIC/LINE IN to STEREO OUT

Please correct the specifications on pages 15 and 16 of the *Owner's Manual* and on page 8 of the *Setup Guide* as follows:

Analog I/O**INSERT Return**

Input impedance 10 k ohm

Digital I/O**ADAT/OPTICAL input**

Format ADAT/IEC60958

ADAT/OPTICAL output

Format ADAT/IEC60958

Analog performance**THD (at maximum input level)**

< 0.010% (Hi FS) 1 kHz, MIC/LINE IN to STEREO OUT

Frequency response (at nominal level)

20 Hz - 40 kHz (Hi FS) +0.5 dB/-2.0 dB, MIC/LINE IN to STEREO OUT