



Performing a Clean Uninstall in Windows 98 SE/ME

Under some troubleshooting or update circumstances, users may wish to reproduce a “fresh installation” condition on a particular PC. In other words, you might want the computer to be in the state it was in before the US-428 was installed for the first time.

If you want to perform a fresh reinstall, here’s how to uninstall all references to the US-428 in the computer. *NOTE:* Depending on the driver version installed on the PC in question, not all files listed in this document will appear in your installation.

- A. Delete any of the following files that may appear in C:\WINDOWS\SYSTEM32\DRIVERS:
 - EZUSB.SYS
 - PROG8000.SYS
 - US428DLL.SYS
 - US428.SYS
 - US428WDM.SYS
- B. Delete any of the following files that appear in C:\WINDOWS\INF:
 - US428TST.INF
 - US428.INF
- C. Delete any of the following files from C:\WINDOWS\INF\OTHER:
 - TASCAMUS428TST.INF
 - TASCAMUS428.INF
- D. Delete files DRVIDX.BIN and DRVDATA.BIN from C:\WINDOWS\INF. (Don’t worry, Windows can rebuild them from the INF files next time a device is loaded.)
- E. In Device Manager, find TASCAM US-428 and delete it from the device tree.
- F. Run the Registry Edit (START/RUN, type REGEDIT). Check the following keys:
 - Under the key HKEY_LOCAL_MACHINE\ENUMUSB, delete the entries
 - \VID_1604 (TEAC)
 - \VID_0547 (ANCHOR CHIPS)
 - Delete the key HKEY_LOCAL_MACHINE\ENUMUS428

(Note that you may not have all these files, depending on which version of the US-428 drivers you are uninstalling.)

- G. The next time Windows sees a US-428 it will run the New Hardware Wizard.