

CONSULTANT'S AND SYSTEM DESIGN SPECIFICATION



The TASCAM CD-RW901 is a 3U rack-mountable dual-well CD Player (well #1), CD player/recorder (well #2). Both decks have independent meters, 12 character text display, and each has a multi-purpose dial. Both decks are capable of auto-ready (pause at each track ID), fader start, EOM alerts, and shutter-scrub (jog mode) via multi-dial. Both wells utilize a rugged TEAC computer drive.

The CDRW-402 offers parallel control and tally messages. User selectable Fade In/Out. CD-Text and transport control is achieved via FS/2 keyboard (input on front panel). A headphone output w/volume control allows monitoring of individual or both wells.

Well #1 – **(player)** Features 9 +/- pitch control, two-locate points, and call. Track advance and rewind are located on the multi-purpose dial. Dedicated analog outputs via balanced XLR connectors and unbalanced RCA jacks. S/PDIF Optical and Coax digital outputs.

Well #2 – **(player/recorder)** Features sync record, record mute, and call. Track advance and rewind are located on the multi-purpose dial. Dedicated analog inputs and outputs via balanced XLR connectors and unbalanced RCA jacks. S/PDIF Optical and Coax digital outputs.

A common unbalanced RCA output is provided. Wired remote control (RC-402) is included.